

KBox A-150-BYT



DIN RAIL Industrial Computer Platform for Control & Process Optimization

- ▶ High performance with Intel® Celeron® J1900 Quad Core™ processor
- ▶ Fanless passive cooling, turnable heatsink optional
- ▶ Flexible DIN RAIL mounting
- ▶ Broad range of interfaces and expansion capabilities
- ▶ Supports Kontron APPROTECT based on WIBU Systems Technology optionally

KBox A-150-BYT

DIN RAIL Embedded Box PC

Developed specifically for control cabinet applications the new KBox A-150-BYT offers flexible DIN Rail mounting positions even when space is limited. The fanless design ensures a significantly prolonged lifespan and high system availability.

The KBox A-150-BYT offers high processor performance at low power dissipation by an Intel® Celeron® J1900 Quad Core processor.

The KBox A-150-BYT supports Kontron's Security Solution APPROTECT based on WIBU Systems Technology on request. In tandem with a specifically developed software framework, it provides full IP and copy/reverse engineering protection through its optional WIBU-Systems security chip.

The KBox A-150-BYT is Microsoft Azure Certified, which makes it perfectly suited for working with Microsoft Azure IoT services.

► TECHNICAL INFORMATION

PROCESSOR	CPU SPEED BIOS	Intel® Celeron® J1900 Quad Core 2.0/2.4 GHz (Burst) AMI® Aptio V5
MEMORY	TECHNOLOGY MAX. CAPACITY	DDR3L 8 GByte
INTERFACES	GRAPHICS PORTS USB ETHERNET SERIAL PORTS	VGA, HDMI 2x USB 2.0 1x USB 3.0 2x 10/100/1000 2x RS232/422/485 2x RS232 option
STORAGE	mSATA SSD	Max. 512 GByte optional drive bay for 2.5" Slim SSD
EXPANSION	MINI PCIe/ PCIe	1x mPCIe
SOFTWARE SUPPORT	MICROSOFT WINDOWS LINUX	Windows 7 incl. Emb., Windows 8.1, Windows 10 IoT Ubuntu
POWER	INPUT VOLTAGE RANGE	9...30 VDC direct
MECHANICAL	CONSTRUCTION MOUNTING DIMENSIONS (W x H x D) WEIGHT	Steel DIN RAIL 180 x 50 x 134 mm (with drive bay: H 58 mm) ca. 1.0 kg
ENVIRONMENT	COOLING OPERATING TEMPERATURE RELATIVE HUMIDITY	Fanless passiv 0 °C - 50 °C ambient 10 %-90 % @ 39 °C, non condensing
APPROVALS	CERTIFICATIONS	CE, Safety EN60950, Emission EN55022 class B

► Global Headquarters

Kontron S&T AG

Lise-Meitner-Str. 3-5
86156 Augsburg, Germany
Tel.: + 49 821 4086 0
Fax: + 49 821 4086 111
info@kontron.com
www.kontron.com